

Aficio™ MP 2851/3351/4001/5001

COPIER

Copying process:	Single laser beam scanning & electro-photographic printing
Copy speed:	28/33/40/50 copies per minute
Resolution:	600 dpi
Warm-up time:	22 seconds
First output speed:	4.5/4.5/4.1/3.5 seconds
Memory:	Maximum: 768 MB + 40 GB HDD
Paper input capacity:	Maximum: 3,100/3,100/4,400/4,400 sheets
Paper output capacity:	Maximum: 1,625/1,625/3,625/3,625 sheets
Paper size:	A5 - A3
Paper weight:	52 - 157/157/220/220 g/m ²
Dimensions (W x D x H):	MP 2851/3351: 570 x 653 x 709 mm MP 4001/5001: 670 x 677 x 910 mm
Weight:	Less than 65/65/85/85 kg
Power source:	220 - 240 V, 50 - 60 Hz
Power consumption:	Operation: Less than 1.4/1.4/1.5/1.5 kW

PRINTER

Print speed:	28/33/40/50 prints per minute
Printer language:	Standard: PCL5e, PCL6 Option: Adobe® PostScript® 3™, IPDS
Resolution:	Maximum 600 x 600 dpi
Interface:	Standard: USB 2.0, Ethernet 10 base-T/100 base-TX, Option: IEEE 1284/ECP, Wireless LAN (IEEE 802.11a/g, WPA support), Bluetooth, Gigabit Ethernet
Network protocol:	TCP/IP (IPv4, IPv6), IPX/SPX, AppleTalk
Supported environments:	Windows® 2000/XP/Vista/7/Server 2003/Server 2008, Novell® NetWare® 3.12/3.2/4.1/4.11/5.0/5.1/6/6.5, UNIX Sun® Solaris 2.6/7/8/9/10, HP-UX 10.x/11.x/11iv2, SCO OpenServer 5.0.6/5.0.7/6.0, RedHat® Linux 6.x/7.x/8.x/9.x/Enterprise, IBM® AIX v4.3/5L v5.1/5L v5.2/5.3, Macintosh 8.6 or later (OS X Classic), Macintosh X v10.1 or later (OS X native), SAP® R/3® (3.x or later), mySAP ERP2004 or later, NDPS Gateway Netware 5.1 (SP8 or later)/6.0 (SP5 or later)/6.5 (SP3 or later), IBM® iSeries / AS/400 using OS/400 Host Print Transform

SCANNER

Scan speed:	Full colour : Maximum 37/37/39/39 ppm B/W: Maximum 53/53/69/69 ppm
Resolution:	Maximum 600 dpi (TWAIN: 1,200 dpi)
Original size:	A5 - A3
Bundled drivers:	Network TWAIN
Scan to e-mail:	SMTP, TCP/IP
Scan to folder:	SMB, FTP, NCP protocol (with login security)

SOFTWARE SOLUTIONS

SmartDeviceMonitor™, Web SmartDeviceMonitor™, Web Image Monitor, DeskTopBinder™ Lite

FAX (OPTION)

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3, ITU-T (T.37) Internet Fax, ITU-T (T-38) IP Fax
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	39/39/56/56 cpm (A4/SEF)
Memory capacity:	12 MB standard, 44 MB max.
Memory backup:	Yes

OTHER OPTIONS

2 x 500-sheet paper trays (MP 2851/3351), 2 x 550-sheet paper trays (MP 4001/5001), 1,200-sheet LCT (MP 4001/5001), 2,000-sheet LCT, 125-sheet one-bin tray, Internal shift tray (MP 2851/3351), 500-sheet finisher (MP 2851/3351), 1,000-sheet finisher, 3,000-sheet finisher (MP 4001/5001), 1,000-sheet booklet finisher (MP 2851/3351), 2,000-sheet booklet finisher (MP 4001/5001), Punch kits (2/4 switchable hole punch, Scandinavian 4 hole punch), Bridge unit, Data Overwrite Security Unit, Copy Data Security Unit, HDD Encryption Unit, File format converter, Browser unit, Key counter bracket, Counter interface unit, GlobalScan NX, Scanner Accessibility Unit (MP 4001/5001), Fax marker, 2nd Super G3 port, Low cabinet, Card authentication package, Professional software solutions

Ricoh has designed these products to meet EC ENERGY STAR guidelines for energy efficiency.

For availability of models, options and software, please consult your local Ricoh supplier.



RICOH



For more information, please contact

First Class Business Solutions