

MP C305SP/MP C305SPF

MAIN SPECIFICATIONS

Aficio®

GENERAL

Warm-up time:	23 seconds
First output speed:	Full colour: 11 seconds B/W: 7 seconds
Continuous output speed:	Full colour: 30 pages per minute B/W: 30 pages per minute
Memory:	Maximum: 1 GB
Dimensions (W x D x H):	498 x 532 x 505 mm
Weight:	45 kg
Power source:	220 - 240 V, 50/60 Hz

COPIER

Copying process:	Dry electrostatic transfer system
Multiple copying:	Up to 99 copies
Resolution:	600 dpi
Zoom:	From 25% to 400% in 1% steps

PRINTER

Printer language:	Standard: PCL5c, PCL6, Adobe® PostScript® 3™
Print resolution:	300 dpi, 600 dpi, 1,200 dpi
Interface:	Standard: USB 2.0, Ethernet 10 base-T/100 base-TX Option: Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Gigabit Ethernet
Network protocol:	Standard: TCP/IP Option: IPX/SPX
Windows® environments:	Windows® XP, Windows® Vista, Windows® 7, Windows® Server 2003, Windows® Server 2008, Windows® Server 2008R2
Mac OS environments:	Macintosh OS X Native v10.2 or later
UNIX environments:	UNIX Sun® Solaris, HP-UX, SCO OpenServer, RedHat® Linux, IBM® AIX
Novell® Netware® environments:	v6.5
SAP® R/3® environments:	SAP® R/3 3.x® or later

SCANNER

Scanning speed:	Full colour: Maximum 30 originals per minute B/W: Maximum 30 originals per minute
Resolution:	100 dpi, 200 dpi, 300 dpi, 400 dpi, 600 dpi
Original size:	A4, A5, B5
File format:	Single page TIFF, Single page JPEG, Single page PDF, Single page High compression PDF, Single page PDF-A, Multi page TIFF, Multi page PDF, Multi page High compression PDF, Multi page PDF-A
Bundled drivers:	Network TWAIN
Scan to:	E-mail: SMTP, POP, IMAP4 Folder: SMB, FTP, NCP (Option)

FAX

Circuit:	PSTN, PBX
Compatibility:	ITU-T (CCITT) G3
Resolution:	8 x 3.85 line/mm, 200 x 100 dpi 8 x 7.7 line/mm, 200 x 200 dpi
Transmission speed:	G3: 2 second(s) (200 x 100 dpi, JBIG)
Modem speed:	Maximum: 33.6 Kbps
Scanning speed:	2.4 second(s)
Memory capacity:	4 MB
Memory backup:	Yes

PAPER HANDLING

Recommended paper size:	Standard paper tray(s): A4, A5 Bypass tray: A4, A6
Paper input capacity:	Maximum: 1,350 sheets
Paper output capacity:	Maximum: 200 sheets
Paper weight:	Standard paper trays: 60 - 163 g/m² Bypass tray: 60 - 220 g/m² Duplex tray: 60 - 163 g/m²

ECOLOGY

Power consumption:	Maximum: 1.2 kW Ready mode: 45 W Sleep mode: 1.2/1.3 W TEC (Typical Electricity Consumption): 1,170/1,191 W/h
--------------------	--

SOFTWARE

Standard:	SmartDeviceMonitor Web SmartDeviceMonitor® Web Image Monitor
Optional:	Unicode Font Package for SAP

OPTIONS

Platen cover, ARDF, 2 x 500-sheet paper tray, One-bin tray, Cabinet, Hard Disk Drive, Bi-directional IEEE 1284, Wireless LAN (IEEE 802.11a/g), Bluetooth, Gigabit Ethernet, VM Card, Netware, Pictbridge, Browser unit, Counter interface, File format converter, Copy Data Security Unit, Fax board

For availability of models, options and software, please consult your local Ricoh supplier.



ISO9001 certified, ISO14001 certified, ISO27001 certified

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear.

Copyright © 2012 Ricoh Europe PLC. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Europe PLC.

www.ricoh-europe.com

RICOH
imagine. change.

For more information,
please contact