

RICOH MP W6700SP

MAIN SPECIFICATIONS

GENERAL

Technology:	Electro-photographic printing
Fusing:	Heat and pressure
Toner Type:	Magnetic brush dual component dry toner system
Print Speed:	3.3 ppm @A0/E SEF 6.7 ppm @A1/D LEF
Print Resolution:	RPCS (Emulation): 600 dpi PS3/PDF: 600/300 dpi RP-GL/GL2: 600/400 dpi RTIFF: 600/400/300/200 dpi
Warm-up time:	Less than 120 seconds (23 degrees Celsius)
First Copy Time:	18 sec @ A1/D LEF (Roll Feeder)
Maximum Copy Size:	(Metrics) 914 mm x 15,000 mm (Roll Feeder) 914 mm x 2,000 mm (Bypass) (Inches) 36" x 590.55" (Roll Feeder) 36" x 70.74" (Bypass)
Copy Speed:	6.7 cpm / ppm @ A1/D LEF
Minimum Copy size:	(Metrics) 210 mm x 210 mm (Roll Feeder) 210 mm x 182 mm (Bypass) (Inches) 8.27" x 8.27" (Roll Feeder) 8.27" x 7.17" (Bypass)
Dimensions (WxDxH):	1250 x 755 x 1215 mm
Weight:	230 kg
Power Source:	220V - 240V/ 8A 50/60Hz
Power Consumption:	1.84 Kw

SCANNER FEATURE

Colour Scanner	
Optical Resolution:	Scan to email/folder: 150 / 200* / 300 / 400 / 600* dpi, *Default for scan 200 dpi, for copy 600 dpi Resolution: 150 to 2400 dpi (Copy) 150 to 1200 dpi (Scan)
Scan Mode:	Mono: Drawing mode (Default), Text mode, Text/Photo mode, Text/Drawing mode, Photo mode, Gray scale Color: Text/Photo mode, Photo
Scan Speed:	Mono: 80 mm/s (600 dpi) Colour: 26.7 mm/s (600 dpi)
Maximum Scan Size:	(Metric) 914.4 mm x 15,000 mm (Inches) 36" x 590.55"
Minimum Scan size	(Metric) 210 mm x 210 mm (Inches) 8.27" x 8.27"
Protocol:	Network: TCP/IP Sending E-mail: SMTP AUTH, POP before SMTP Scan to Folder: SMB, FTP, NCP

MEDIA HANDLING

Paper Feeding Capacity:	2 Roll Feeder (Standard): Min Width: 210 mm Max Width: 914 mm (Metric), 37.8" (Inches) Max Length: 150,000 mm (Metric), 590.55" (Inches) Max Diameter: Φ 175 mm Bypass Feed (Standard): 1 sheet
-------------------------	---

Paper Output Capacity:	Inner: 99 sheets @ A1/D LEF (plain paper) (Larger than A1/D size cannot be stacked), 10 sheets @ A1/D LEF (application paper) 1 sheet / film Rear: 10 sheets @ A1/D Portrait, A0/E SEF (plain paper) (Smaller than A2/C size cannot be stacked), 1sheet @ A1/D Portrait, A0/E SEF (application paper), 1sheet @ film
Paper Weight: Roll Paper:	51-134 g/m ²

PRINT CONTROLLER SPECIFICATION

Configuration:	Embedded
CPU:	Calpella (1.06 GHz)
Memory:	2.5 GB
HDD:	320 GB (Shared with Copy/Printer/ Scanner applications)
Operating System:	PS Driver Windows Vista/7/8/8.1/10/2003server/2008server/2008R2server/2012server/2012serverR2 Mac OS (later than Mac OS10.7)
Network Protocol:	TCP/IP (IPv4, IPv6), IPX/SPX (option); Auto switching available
Supported Print Language:	PostScript Level3 (PDF), RPCS, Emulation: HP-GL, HP-GL/ 2(HP-RTL), TIFF(CALS)
Font:	(PS) European 136 fonts
Network Interface:	Standard: Ethernet 10/100BaseTX Option: Wireless LAN (802.11a/b/g/n)
Interface Slot:	Option Slot: 2 Slot USB-Host Slot: USB 2.0 host

OTHER OPTIONS

Multi Stacker Type 7140
Double Stacker Type 7140
Original Tray Type G
Roll Paper Holder Unit Type A
Original Hanger
IEEE802.11a/g/n Interface Unit Type M2

ENVIRONMENTAL INFORMATION

Complies with Energy Star 1.1 standards. EPEAT 'GOLD'

RICOH
imagine. change.

www.ricoh-ap.com

RICOH ASIA PACIFIC PTE LTD

103 Penang Road #08-01/07, VISIONCREST Commercial, Singapore 238467
Phone: +65 6830 5888, Fax: +65 6830 5830

All brand and/or product names are trademarks of their respective owners. Specifications and external appearance are subject to change without notice. The colour of the actual product may vary from the colour shown in the brochure. The images in this brochure are not real photographs and slight differences in detail might appear. Copyright © 2015 Ricoh Asia Pacific Pte Ltd. All rights reserved. This brochure, its contents and/or layout may not be modified and/or adapted, copied in part or in whole and/or incorporated into other works without the prior written permission of Ricoh Asia Pacific Pte Ltd.