

SPECIFICATIONS

MP 1100/MP 1350



Printer

Print speed

110/135 prints per minute

Printer language/resolution

Standard: PCL5e: 300/600dpi
PCL6: 600/1,200dpi
RPCS™: 200 - 1,200dpi
Option: Adobe® PostScript® 3™:
600/1,200dpi

Interface

Standard: Ethernet 10 base-T/100 base-TX USB 2.0
Option: Bi-directional IEEE1284
FireWire (IEEE1394)
Wireless LAN (IEEE802.11b)
Gigabit Ethernet
Bluetooth
USB Host

Memory

Standard: 512MB with
additional 256MB
Hard Disk Drive: 320GB (2 x 160GB)

Network protocol

TCP/IP, IPX/SPX, SMB, EtherTalk
(Auto Switching)

Supported networks

Windows® 95/98/Me/NT4.0/2000/XP/
Server 2003
Novell® NetWare® 3.12, 3.2, 4.1, 4.11, 5.0,
5.1, 6, 6.5
UNIX Sun® Solaris 2.6/7/8/9
HP-UX 10.x/11.x
SCO OpenServer 5.0.6
RedHat® Linux 6.x/7.x/8.x
IBM® AIX v4.3/5L v5.1
Macintosh 8.6 - 9.2.x (OS X Classic),
Macintosh X v10.1 or later (native mode)
IBM® System i5™ HPT
mySAP™ ERP



Copier

Copying process

2 x 4-way laser diode array & electro-
photographic printing

Copy speed

110/135 copies per minute

Resolution

Output: 1,200dpi/scan: 600dpi

Multiple copy

Up to 9,999

Warm up time

Less than 360 seconds

First output speed

MP 1100: 3.2 seconds
MP 1350: 3 seconds

Zoom

25 - 400% (in 1% steps)

Memory

Hard Disk Drive: 320GB (2 x 160GB)

Paper input capacity

Standard: 2 x 1,000-sheet tandem trays
2 x 500-sheet paper trays
Maximum: 8,500 sheets

Paper output capacity

Maximum 3,000 sheets

Paper size

Minimum: 100 x 140mm
Maximum: 330 x 458mm

Paper weight

52 - 216g/m²

Duplexing

Standard

Dimensions (W x D x H)

870 x 860 x 1,476mm

Weight

Less than 305kg

Power source

220 - 240V, 50/60Hz

Power consumption

Maximum:
MP 1100: Less than 3.5kW
MP 1350: Less than 4kW



Scanner (Option)

Scan speed

80 originals per minute (A4)

Resolution (B/W and Colour)

100 - 1,200dpi (100 - 600dpi)

Maximum original size

A3+

Output formats

PDF, JPEG, TIFF

Bundled drivers

Network TWAIN

Scan to e-mail

Authentication: SMTP and TCP/IP required
Destination address selection: Via LDAP,
local address book or direct input

Destination addresses

Up to 500 from local address book, up to
100 via LDAP

Stored destination addresses

Maximum 2,000

Scan to folder

Via SMB, FTP or NCP protocol, up to
50 folders per job



Software

Standard: SmartDeviceMonitor™ for
Admin/Client, Web SmartDeviceMonitor™,
Web Image Monitor, DeskTopBinder™ Lite,
ScanRouter™ Lite, TWAIN driver, Printer
utility for Macintosh, Agfa Font Manager
Option: DeskTopEditor For Production,
doc-Q-manager, doc-Q-route, Equitrac
Office™, MicroPress®

Other Options

- 4,550-sheet A4 large capacity tray
- 4,000-sheet A3 large capacity tray
- 500-sheet multi bypass tray
- Dual station cover interposer
- 3,000-sheet finisher with Jogger unit
- Punch unit (2/4 switchable hole
punch, Scandinavian 4 hole punch
only with MP 1100)
- Saddle stitch unit
- Professional booklet maker
- Z-folder
- GBC StreamPunch™ III
- Data Overwrite Security Unit
- Copy Data Security Unit
- File Format Converter
- Copy Connect kit
- Browser unit
- VM card
- Fiery® EB-135 Printer/Scanner
Controller

Company management systems applied during the
manufacturing of all Gestetner products conform to
ISO9001 quality and ISO14001 environmental
management standards.

In compliance with EU RoHS directive
(RoHS: Restriction of Hazardous Substances).

We reserve the right to make amendments to the
technical specifications and external appearance of
this equipment. Please note that the full range of
options shown in this publication may not always be
available. All brand and product names are recognised,
and hereby acknowledged, as registered trademarks of
their respective owners.



Gestetner

Part of the NRG group

www.gestetner.com



GMP1350005600